

Sheave Blocks | 12 – 15 Ton | 420 & 421 | Single Sheave (Hook & Shackle Top)

420 With Hook



421 With Shackle



406 Tailboard



Champion

- Hooks and side plates are forged alloy steel and heat treated.
- Shackles and yokes are forged and heat treated steel.
- All parts are forged.
- Side plates are designed to eliminate possibility of rope jamming.
- Can be furnished with bronze bushings or sealed roller bearings.
- Opening feature permits insertion of rope while block is suspended from gin-pole.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- Hook and shackle assemblies can be interchanged.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue rated.

Specifications

Sheave Diameter (in.)	Bearing Code	Stock No.			Wire Rope Size (in.) [†]	Working Load Limit (ton)*	Weight Each (lbs.)			Rep. Sheave Stock No.	Rep. Latch Stock No.
		420 with hook	421 with shackle	406 Tail Board			420 with hook	421 with shackle	406 Tail Board		
6	BB	169374	169481	167973	3/4 – 7/8	12	40	48	24	460940	1096609
8	BB	169418	169515	167991	3/4 – 7/8	15	51	57	30	461360	1096609
10	BB	110221	110720	103186	3/4 – 7/8	15	63	69	42	462001	1096609

*Ultimate Load is 4 times the Working Load Limit.